



MIST SEPARATOR SUPER SMC - AME 250C

\$169.80 inc. GST

Key Features: AME 250C

- Due to its special configuration, a color change indicated when element is saturated.
- Filtration of compressed air (0.01 μm).
- Operating pressure range 0.05 to 1.0 MPa.
- Temperature range 5 to 60° C.
- Modular connection (AME150C to 550C).
- Port size: Rc3/8
- Max. Flow (l/min): 500
- Max. Flow (m^3/h): 30

[View SMC Catalogue](#)

*Image may differ to actual product



SKU: AME250C-03

Categories: [Compressed Air Filters, Regulators, Lubricators, SMC](#)

PRODUCT DESCRIPTION

Series AME is perfect for filtration of compressed air requiring higher clean air for painting lines, compressed air for clean rooms and/or equipment where oils must be avoided. It captures foreign matter sized 0.01 μm or more and absorbs oil particles in an aerosol state. It also reduces oil smell.

Key Features:

- Due to its special configuration, a color change indicated when element is saturated.
- Filtration of compressed air (0.01 μm).
- Operating pressure range 0.05 to 1.0 MPa.
- Temperature range 5 to 60° C.
- Modular connection (AME150C to 550C).
- Port size: Rc3/8
- Max. Flow (l/min): 500
- Max. Flow (m^3/h): 30

[View SMC Catalogue](#)

*Image may differ to actual product

If you wish to collect your product from our showroom in Canning Vale, please select 'Click & Collect' at check out.

ADDRESS

1/19 Mordaunt Circuit
Canning Vale
Perth 6155

CALL
1300 062 377

FAST DISPATCH

- Tracking number emailed instantly after dispatch
- Your item will be shipped via Courier which requires a signature for collection.
 - Phone number required: Our courier will call to book the delivery day.
- A delivery day, not time: Our discounted rates require you to be home 9am-6pm on the day of delivery. Perhaps a business address is more convenient for you.