



ODOR REMOVAL FILTER SMC - AMF 850

\$1,111.97 inc. GST

Key Features: AMF 850

- Active carbon element with large filtration area.
 - Easy replacement of elements.
 - Filtration degree 0.01 μm .
- 13 layers of active carbon ensure optimum effectiveness.
 - Operating pressure range 0.05 to 1.0 MPa.
 - Temperature range 5 to 60° C.
- Modular connection (AMF150C to 550C).
 - Port size: Rc2
 - Max. Flow (l/min): 12000
 - Max. Flow (m^3/h): 720

[View SMC Catalogue](#)

*Image may differ to actual product



SKU: AMF850-20

Categories: [Compressed Air Filters](#), [Regulators](#), [Lubricators](#), [SMC](#)

PRODUCT DESCRIPTION

Series AMF is perfect for deodorization whereas it eliminates odor and gas ingredients in compressed air. It is designed for use in the area such as a clean room in food processing, pharmaceutical, brewing, and breathing systems where odors must be avoided.

Key Features:

- Active carbon element with large filtration area.
 - Easy replacement of elements.
 - Filtration degree 0.01 μm .
- 13 layers of active carbon ensure optimum effectiveness.
 - Operating pressure range 0.05 to 1.0 MPa.
 - Temperature range 5 to 60° C.
- Modular connection (AMF150C to 550C).
 - Port size: Rc2
 - Max. Flow (l/min): 12000
 - Max. Flow (m^3/h): 720

[View SMC Catalogue](#)

*Image may differ to actual product

If you wish to collect your product from our showroom in Canning Vale, please select 'Click & Collect' at check out.

ADDRESS

1/19 Mordaunt Circuit
Canning Vale
Perth 6155

CALL

1300 062 377

FAST DISPATCH

- Tracking number emailed instantly after dispatch
- Your item will be shipped via Courier which requires a signature for collection.
 - Phone number required: Our courier will call to book the delivery day.
- A delivery day, not time: Our discounted rates require you to be home 9am-6pm on the day of delivery. Perhaps a business address is more convenient for you.