



## SAMOA 1-1/2" ID SPRING REWIND HOSE REEL 15M CAPACITY

**\$2,657.00 inc. GST**

### Samoa Spring Rewind Hose Reel

The Samoa 508890 heavy duty 1-1/2" spring rewind hose reel is a bare reel and has been designed, engineered & built for maximum durability when fast and efficient very high volume delivery counts.

Accommodating up to 15m of 1-1/2" hose, the extremely robust all metal construction of the 508890 hose reel can be used for low pressure delivery of large volumes of water, diesel and hydraulic oils/lubricants in applications aligned with watering, diesel distribution, lube trucks, mining & construction sites, quarries, marine and aviation.

Manufactured utilising 4mm gauge steel, the wide base arms and shaft form a very rigid and stable structure and the full port, low flow restriction 1-1/2" nickel protected shaft and swivel contributes to reducing fill time and overall improved efficiency.

The Samoa heavy duty 1-1/2" spring rewind hose reel represents the ultimate in large scale hose reel reliability and performance.

Working pressure of 600psi (41bar). Full port 1-1/2" goose neck hose connection eliminates hose collapsing and kinking. Spool mounted on two permanently lubricated ball bearings ensures reduced torque load for smooth operation. Dual power spring for fast and effective hose retrieval. 1-1/2" BSP (f) outlet thread. 1-1/2" BSP (m) inlet thread. Also suitable for use with oil, diesel fuel, water and waste oil.



SKU: 508890

Categories: [Air Hose Reels](#), [Alemlube](#)

## PRODUCT DESCRIPTION

### PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

- Heavy duty extremely robust construction
  - Working pressure of 600psi (40bar)
  - Full port 1-1/2" nickel protected shaft and swivel
- 1-1/2" goose neck hose connection eliminates hose collapsing and kinking
- Spool mounted on two permanent lubricated ball bearings ensures reduced torque load for smooth operation
  - Dual power spring for fast and effective hose coiling
  - Large effective radial latching area
- Zinc plated steel hose outlet rollers for maximum durability
- Polyester powder coated for increased wear and weather resistance Outlet assembly can be mounted in 2 positions

- Outlet thread: 1-1/2" BSP(f)
- Inlet thread: 1-1/2" BSP(m)
  - Weight: 55kg

If you wish to collect your product from our showroom in Canning Vale, please select 'Click & Collect' at check out.

**ADDRESS**

1/19 Mordaunt Circuit  
Canning Vale  
Perth 6155

**CALL**

1300 062 377

**FAST DISPATCH**

- Tracking number emailed instantly after dispatch
- Your item will be shipped via Courier which requires a signature for collection.
  - Phone number required: Our courier will call to book the delivery day.
- A delivery day, not time: Our discounted rates require you to be home 9am-6pm on the day of delivery. Perhaps a business address is more convenient for you.